MSDS Material Safety Data Sheet
Blended Waxes, Inc.

BW-450 Paraffin

MSDS Number: 019 Revision Date: 4/1/09

1 PRODUCT AND COMPANY IDENTIFICATION

Manufacturer

Blended Waxes, Inc.
1512 S. Main Street
P.O. Box 3044
Oshkosh, WI 54902

Contact: Lab
Telephone Number: (920) 236-8080
FAX Number: (920) 236-8081
Web www.blendedwaxes.com

Product Use

Candle making and as a wax-blending material.

2 HAZARDS IDENTIFICATION

Route of Entry: Inhalation; Skin
Target Organs: NA
Inhalation: Fumes from molten material may cause mild respiratory irritation
Skin Contact: Contact with molten material may cause burns
Eye Contact: Yes, when product is molten.
Ingestion: Ingestion is not an applicable route of entry for intended use.

NFPA-ratings (scale 0-4): Health = 1, Fire = 1, Reactivity = 0

3 COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients:

Cas #	Perc.	Chemical Name
8002742	100%	Paraffin wax fume

4 FIRST AID MEASURES

Inhalation: If symptoms develop, move victim to fresh air. If symptoms persist, seek medical attention.
Skin Contact: Promptly flush skin with water and seek medical attention.
Eye Contact: Immediately seek medical attention.
Ingestion: Product is non-toxic. Should stomach discomfort occur, seek medical attention.

5 FIRE FIGHTING MEASURES

6 ACCIDENTAL RELEASE MEASURES

Dike or contain molten material. Allow material to solidify, then scrape up solid material. Handle as solid waste clean up. Clean up solid spills to prevent slippery surface conditions.

7 HANDLING AND STORAGE

Handling Precautions: Handle with care and avoid spillage on the floor (slippage).
Storage Requirements: Store in cool, dry area away from heat or direct sunlight.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls: Use local exhaust at filling zones and where leakage is probable. Use mechanical (general) ventilation for storage areas.
Protective Equipment: HMIS PP, B | Goggles, Gloves
Exposure Guidelines/Other: Additional protective clothing and/or equipment as required to prevent contact with molten wax. Provide adequate ventilation to avoid build up of fumes.

9 PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	White, waxy		
Physical State:	Solid	**Boiling Point:**	
Odor:	Low	**Freezing/Melting Pt.:**	132 F
pH:	NA	**Solubility:**	Nil. <.1%
Vapor Pressure:	NA	**Spec Grav./Density:**	<.84
Vapor Density:	NA		

10 STABILITY AND REACTIVITY

Stability: Product is stable under normal conditions.
Conditions to avoid: Avoid heating above 300 F to prevent build-up of fumes.
Materials to avoid (incompatability): Strong Oxidizing Agents.
Hazardous Decomposition products: CO, CO2 and unidentified byproducts of combustion.
Hazardous Polymerization: Will Not Occur

11 TOXICOLOGICAL INFORMATION

NA

12 ECOLOGICAL INFORMATION

NA

13 DISPOSAL CONSIDERATIONS

Incineration or burial in accordance with local, state and federal regulations.

14 TRANSPORT INFORMATION

Not hazardous product according to DOT classifications.

15 REGULATORY INFORMATION

```
COMPONENT / (CAS/PERC) / CODES
---------------------------------------------------------------
*Paraffin wax fume (8002742 100%) MASS, OSHAWAC, PA, TXAIR

REGULATORY KEY DESCRIPTIONS
---------------------------------------------------------------
MASS = MA Massachusetts Hazardous Substances List
OSHAWAC = OSHA Workplace Air Contaminants
PA = PA Right-To-Know List of Hazardous Substances
TXAIR = TX Air Contaminants with Health Effects Screening Level
```

16 OTHER INFORMATION

Disclaimer:
Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained herein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for their particular purpose(s).

END OF MSDS DOCUMENT